

6 3/4" (171mm) GX542 Assembly: 970024 IADC: 5-4-2

DESIGN SPECIFICATION

Type: Bearing Type: Configuration: Cutting Structure: Gage Rows: Inner Rows: Nose Rows: Bevel Rows: Head Type: Hardfacing: Armor: Head Feature: Bit Connection: Circulation Type: Bit Weight:

Tri-cone Air Circulation Roller-Ball-Roller TCI Conical Conical Conical Round Full Armor Standard Round (TCI) Fluid Dynamic Profile 3 1/2" Reg. API Jet Nozzle 44 lbs / 20 kg

GENERAL OPERATING PARAMETERS

Rotary Speed: Weight on Bit: 40 – 70 rpm 10,000 – 40,000 lbs

DRILLING APPLICATION

PDB Tools Inc. provides advanced technical products and solutions for the mining, exploration, construction, water well, oil and gas industries. The **6** 3/4" GX542 blasthole bits are designed for drilling soft to medium formations, with rock compressive strength ranging from 10,000 to 25,000 psi. Formation drilled may consist of shale, soft limestone, mudstone, soft slate, gypsum and sandstone. Designed with the latest technology and manufacturing, PDB Tools rock bits are the next evolution.

Innovation, Performance and Value





Grapevine, Texas 76051 • USA *Tel:* 214-295-6324 • *Fax:* 214-295-4493