

9" (229mm) GX432 Assembly: 970055 IADC: 4-3-2

DESIGN SPECIFICATION

Type: Bearing Type: Configuration: Cutting Structure: Gage Rows: Inner Rows: Nose Rows: Bevel Rows: Head Type: Hardfacing: Armor: Head Feature: Bit Connection: Circulation Type: Bit Weight: Tri-cone Air Circulation Roller-Ball-Roller TCI Wedge Conical Conical Round Full Armor Standard Round (TCI) Fluid Dynamic Profile 4 1/2" Reg. API Jet Nozzle 95lbs / 43 kg

GENERAL OPERATING PARAMETERS


Rotary Speed: Weight on Bit: 50 – 90 rpm 10,000 – 35,000 lbs

DRILLING APPLICATION

PDB Tools Inc. provides advanced technical products and solutions for the mining, exploration, construction, water well, oil and gas industries. The **9" GX432** blasthole bits are designed for drilling soft formations, with rock compressive strength ranging from 5,000 to 20,000 psi. Formation drilled may consist of medium shale, clay, mudstone, gypsum and medium calcites. Designed with the latest technology and manufacturing, PDB Tools rock bits are the next evolution.

Innovation, Performance and Value





Grapevine, Texas 76051 • USA *Tel:* 214-295-6324 • *Fax:* 214-295-4493