



10 5/8" (270mm) GX432

Assembly: 970066

IADC: 4-3-2

DESIGN SPECIFICATION

Type:	Tri-cone
Bearing Type:	Air Circulation
Configuration:	Roller-Ball-Roller
Cutting Structure:	TCI
Gage Rows:	Wedge
Inner Rows:	Conical
Nose Rows:	Conical
Bevel Rows:	Round
Head Type:	Full Armor
Hardfacing:	Standard
Armor:	Round (TCI)
Head Feature:	Fluid Dynamic Profile
Bit Connection:	6 5/8" Reg. API
Circulation Type:	Jet Nozzle
Bit Weight:	174 lbs / 79 kg

GENERAL OPERATING PARAMETERS

Rotary Speed:	50 – 120 rpm
Weight on Bit:	15,000 – 50,000 lbs

DRILLING APPLICATION

PDB Tools Inc. provides advanced technical products and solutions for the mining, exploration, construction, water well, oil and gas industries. The **10 5/8" GX432** blasthole bits are designed for drilling soft formations, with rock compressive strength ranging from 5,000 to 20,000 psi. Formation drilled may consist of shale, clay, mudstone, gypsum and soft to medium calcites. Designed with the latest technology and manufacturing, PDB Tools rock bits are the next evolution.

Innovation, Performance and Value

